




America

CERTIFICATE

No. U8 107420 0004 Rev. 01

Holder of Certificate: **Bullfrog International LC**
 7017 West 11800 South
 Herriman UT 84096
 USA

Certification Mark:



Product: Whirlpool spa
 Self-Contained Spa

This product was voluntarily tested to the relevant safety requirements referenced on this certificate. It can be marked with the certification mark above. The mark must not be altered in any way. This product certification system operated by TÜV SÜD America Inc. most closely resembles system 3 as defined in ISO/IEC 17067. Certification is based on the TÜV SÜD "Testing and Certification Regulations". TÜV SÜD America Inc. is an OSHA recognized NRTL for USA and a Standards Council of Canada ISO/IEC 17065 accredited Certification body for Canada.

Test report no.: 095-72162234-100

Date, 2022-04-21

(Liyuan (Mandy) Zhao)



America

CERTIFICATE

No. U8 107420 0004 Rev. 01

Model(s):

Series A:	A5L, A6, A6L, A7, A7L, A8, A8L, A8D, A9L
Series R:	R5L, R6, R6L, R7, R7L, R8, R8L
Series STIL:	STIL5, STIL7, S150
Series X:	X5L, X6L, X6R, X7, X7L, X8, X8L
Series Z:	Triton, Poseidon, Venus, Aurora, Vesta, Terra
Series M:	M6, M7, M8, M9

Brand Name: bullfrog

Tested according to: UL 1563:2009/R:2020-09
CAN/CSA-C22.2 No. 218.1:2013

Parameters:

Rated Input Voltage:	See table on pages 3-5 for model information
Rated Frequency:	60 Hz
Input Current:	See table on pages 3-5 for model information
Protection Class:	I
Degree of Protection:	IPX5
Ambient Temperature:	25°C

Installation Requirements:

1. This equipment must be installed in accordance with the manufacturer's instructions.
2. The Installation of this equipment must be in accordance with the requirements for electrical installations according the relevant authority having jurisdiction.
3. The cautions and warnings in the user's manual for this equipment are considered limitations on the scope of use for purposes of this approval.



America

CERTIFICATE

No. U8 107420 0004 Rev. 01

Model Variant

Models	Rating	Dimension	Capacity	Dry Weight	Weight Filled with Cover	Pump (s)
A5L	240 VAC, 60 Hz, 24/40 A Optional: 120 VAC, 60 Hz, 12 A	5'8" x 7'0" x 31" (1.73 x 2.08x 0.79 m)	243 gal 920 L	455 lbs. 206 kg	3076 lbs. 1,395 kg	2
A6	240 VAC, 60 Hz, 24/40 A	6'8" x 7'4" x 34" (2.03 x 2.24 x 0.86 m)	359 gal 1,360 L	575 lbs. 261 kg	4267 lbs. 2,098 kg	2
A6L	240 VAC, 60 Hz, 24/40 A	6'8" x 7'4" x 34" (2.03 x 2.24 x 0.86 m)	350 gal 1,324 L	575 lbs. 261 kg	4552 lbs. 2,064 kg	2
A7	240 VAC, 60 Hz, 24/40 A	7'4" x 7'4" x 36" (2.24 x 2.24 x 0.91 m)	440 gal 1,666L	661 lbs. 300 kg	5300 lbs. 2,404 kg	2
A7L	240 VAC, 60 Hz, 24/40 A	7'4"x 7'4"x 36" (2.24 x 2.24 x 0.91 m)	434 gal 1,643 L	680 lbs. 308 kg	5253 lbs. 2,383 kg	2
A8	240 VAC, 60 Hz, 24/40 A	7'10" x 7'10" x 38" (2.39 x 2.39 x 0.97 m)	540 gal 2,044 L	758 lbs. 344 kg	6310 lbs. 2,862 kg	2
A8L	240 VAC, 60 Hz, 24/40 A	7'10" x 7'10" x 38" (2.39 x 2.39 x 0.97 m)	504 gal 1,908 L	778 lbs. 353 kg	6053 lbs. 2,746 kg	2
A8D	240 VAC, 60 Hz, 24/40 A	7'10" x 7'10" x 38" (2.39 x 2.39 x 0.97 m)	512 gal 1,938 L	763 lbs. 346 kg	6105 lbs. 2,769 kg	2
A9L	240 VAC, 60 Hz, 40/48 A	9' x 7'10" x 38" (2.74 x 2.39 x 0.97 m)	596 gal 2256.1 L	910 lbs. 412.76 kg	6938.7 lbs. 3147.3 kg	3
R5L	240 VAC, 60 Hz, 24/40 A Optional: 120 VAC, 60 Hz, 12 A	5'8" x 7'0" x 31" (1.73 x 2.08 x 0.79 m)	243 gal 920 L	455 lbs. 206 kg	3076 lbs. 1,395 kg	1
R6	240 VAC, 60 Hz, 24/40 A	6'8" x 7'4" x 34" (2.03 x 2.24 x 0.86 m)	359 gal 1,360 L	575 lbs. 261 kg	4267 lbs. 2,098 kg	2
R6L	240 VAC, 60 Hz, 24/40 A	6'8" x 7'4" x 34" (2.03 x 2.24 x 0.86 m)	446 gal 1,688 L	575 lbs. 261 kg	5155 lbs. 2,338 kg	2
R7	240 VAC, 60 Hz, 24/40 A	7'4" x 7'4" x 36" (2.24 x 2.24 x 0.91 m)	440 gal 1,666 L	661 lbs. 300 kg	5300 lbs. 2,404 kg	2
R7L	240 VAC, 60 Hz, 24/40 A	7'4" x 7'4" x 36" (2.24 x 2.24 x 0.91 m)	434 gal 1,643 L	680 lbs. 308 kg	5253 lbs. 2,383 kg	2



America

CERTIFICATE

No. U8 107420 0004 Rev. 01

Models	Rating	Dimension	Capacity	Dry Weight	Weight Filled with Cover	Pump (s)
R8	240 VAC, 60 Hz, 24/40 A	7'10" x 7'10" x 38" (2.39 x 2.39 x 0.97 m)	540 gal 2,044 L	758 lbs. 343.8 kg	6,310 lbs. 2,862 kg	2
R8L	240 VAC, 60 Hz, 24/40 A	7'10" x 7'10" x 38" (2.39 x 2.39 x 0.97 m)	504 gal 1,908 L	778 lbs. 352.9 kg	6,053 lbs. 2,746 kg	2
STIL5	240 VAC, 60 Hz, 24/40 A Optional: 120 VAC, 60 Hz, 16 A	82" x 66.5" x 30.75" (2.08 x 1.68 x 0.78 m)	256 gal 969 L	475/468 lbs. 215/212 kg	2,611/2,604 lbs 1,184/1,181 kg	1
STIL7	240 VAC, 60 Hz, 24/40 A	85" x 88" x 34" (2.15 x 2.23 x 0.86 m)	392 gal 1483 L	615 lbs. 279 kg	5053 lbs. 2,292 kg	1
X5L	240 VAC, 60 Hz, 24/40 A Optional: 120 VAC, 60 Hz, 12 A Or 120 VAC, 60 Hz, 16 A	5'8" x 7'0" x 31" (1.73 x 2.13 x 0.79 m)	243 gal 920 L	455 lbs. 206.4 kg	3,076 lbs. 1,395 kg	1
X6L	240 VAC, 60 Hz, 24/40 A	6'8" x 7'4" x 34" (2.03 x 2.24 x 0.86 m)	314 gal 1,188 L	575 lbs. 261 kg	4285 lbs. 1,942 kg	2
X6R	240 VAC, 60 Hz, 24/40 A Optional: 120 VAC, 60 Hz, 12 A Or 120 VAC, 60 Hz, 16 A	6'7" x Rnd. x 34" (2.01 x Rnd. x 0.86 m)	291 gal 1,101 L	503 lbs. 228 kg	3,140 lbs. 1,424 kg	1
X7	240 VAC, 60 Hz, 24/40 A	7'4" x 7'4" x 36" (2.24 x 2.24 x 0.91 m)	395 gal 1,495 L	661 lbs. 300 kg	4924 lbs. 2,233 kg	2
X7L	240 VAC, 60 Hz, 24/40 A	7'4" x 7'4" x 36" (2.24 x 2.24 x 0.91 m)	389 gal 1,472 L	680 lbs. 308 kg	4877 lbs. 2,212 kg	2
X8	240 VAC, 60 Hz, 24/40 A	7'10" x 7'10" x 38" (2.39 x 2.39 x 0.97 m)	486 gal 1,839 L	758 lbs. 344 kg	5860 lbs. 2,658 kg	2
X8L	240 VAC, 60 Hz, 24/40 A	7'10" x 7'10" x 38" (2.39 x 2.39 x 0.97 m)	450 gal 1,703 L	778 lbs. 353 kg	5602 lbs. 2,541 kg	2
Triton	240 VAC, 60 Hz, 24/40 A	7'7" x 7'7" x 38" (2.31 x 2.31 x 0.97 m)	465 gal 1,760 L	758 lbs. 344 kg	5860 lbs. 2,548 kg	2
Poseidon	240 VAC, 60 Hz, 24/40 A	7'7" x 7'7" x 38" (2.31 x 2.31 x 0.97 m)	454 gal 1,719 L	778 lbs. 353 kg	5602 lbs. 2,541 kg	2
Venus	240 VAC, 60 Hz, 24/40 A	6'8" x 7'4" x 36" (2.03 x 2.24 x 0.91 m)	387 gal 1,465 L	575 lbs. 261 kg	4625 lbs. 2,098 kg	2
Aurora	240 VAC, 60 Hz, 24/40 A	6'8" x 7'4" x 36" (2.03 x 2.24 x 0.91 m)	379 gal 1,435 L	575 lbs. 261 kg	4552 lbs. 2,064 kg	2



America

CERTIFICATE

No. U8 107420 0004 Rev. 01

Models	Rating	Dimension	Capacity	Dry Weight	Weight Filled with Cover	Pump (s)
Vesta	240 VAC, 60 Hz, 24/40 A	7'0" x 7'0" x 34" (2.08 x 2.08 x 0.86 m)	358 gal 1,355 L	661 lbs. 200 kg	4925 lbs. 2,234 kg	1
Terra	240 VAC, 60 Hz, 24/40 A	7'0" x 7'0" x 34" (2.08 x 2.08 x 0.86 m)	350 gal 1,395 L	680 lbs. 308 kg	4877 lbs. 2,212 kg	1
M7	240 VAC, 60 Hz, 24/40 A	7'7" x 7'7" x 37" (2.31 x 2.31 x 0.94)	456 gal 1,723 L	761 lbs. 345 kg	5757 lbs. 2611 kg	2
M8	240 VAC, 60 Hz, 40/48 A	7'10" x 7'10" x 38" (2.39 x 2.39 x 0.96)	473 gal 1,787 L	834 lbs. 378 kg	6084 lbs. 2743 kg	3
M9	240 VAC, 60 Hz, 40/48 A	9'2" x 7'10" x 38" (2.79 x 2.39 x 0.96)	588 GAL 2,223 L	976 lbs. 442 kg	7239 lbs. 3283 kg	3
M6	240 VAC, 60 Hz, 24/40 A	6'8" x 7'7" x 2'10" (2.03 x 2.31 x 0.86)	387 gal. (1465 L)	800 lbs. (363 kg)	800 lbs. (363 kg)	2
S 150	240 VAC, 60 Hz, 40 A	7'10" x 12'8" x 4'4" (2.38 x 3.96 x 1.32)	1190 gal. (4504 L)	1900 lbs. (863 Kg)	11,924 lbs. (5409 Kg)	2